

1829AC Coax - DBS Video Cable



Description:

18 AWG solid .040" bare copper conductor, gas-injected foam polyethylene insulation, Duobond®II and a 60% aluminum braid shield, PVC jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Coax	1
Total Number of Conductors	1
Series Type	Series 6
AWG	18
Stranding	Solid
Conductor Diameter	.040 in.
Conductor Material	BC - Bare Copper
Corrosion Resistance	Yes

INSULATION:

Insulation Material	Gas-injected FPE - Foam Polyethylene
Insulation Diameter	.180 in.

OUTER SHIELD:

Outer Shield Material Trade Name	Duobond® II
Outer Shield Type	Tape/Braid

Outer Shield Material :

Layer Number	Trade Name	Type	Material	% Coverage (%)
1	Bonded Duofoil®	Tape	Bonded Aluminum Foil- Polyester Tape-Aluminum Foil	100
2		Braid	AL-Aluminum	60

Outer Shield % Coverage	100 %
-------------------------	-------

OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
-----------------------	--------------------------

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.270 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:



1829AC Coax - DBS Video Cable

Operating Temperature Range	-40°C To +80°C
Bulk Cable Weight	30 lbs/1000 ft.
Max. Recommended Pulling Tension	80 lbs.
Min. Bend Radius (Install)	2.75 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CATV, CM
CEC/C(UL) Specification	CM

FLAME TEST:

UL Flame Test	UL1581 Vertical Tray
---------------	----------------------

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

ELECTRICAL CHARACTERISTICS:

Nom. Characteristic Impedance	75 +/- 3 Ohms
Nom. Inductance	.097 µH/ft
Nom. Capacitance Conductor to Shield	16.2 pF/ft
Nominal Velocity of Propagation	83 %
Nominal Delay	1.2 ns/ft
Nom. Conductor DC Resistance @ 20 Deg. C	6.4 Ohms/1000 ft
Nominal Outer Shield DC Resistance	9 Ohms/1000 ft

Minimum Structural Return Loss :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Minimum Structural Return Loss (dB)
		950	2250	15

Nom. Attenuation :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Nom. Attenuation (dB/100 ft.)
	5			.5
	55			1.4
	211			2.6
	500			4.1
	750			5.1
	862			5.5
	1000			6.0
	1450			7.9
	1800			8.4
	2250			10.1
	3000			11.0

Max. Attenuation :



1829AC Coax - DBS Video Cable

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Max. Attenuation (dB/100 ft.)
	5			0.67
	55			1.60
	211			2.87
	500			4.48
	750			5.59
	862			5.98
	1000			6.54
	1450			8.30
	1800			9.30
	2250			10.60
	3000			11.90

Max. Operating Voltage - UL 300 V RMS

Other Electrical Characteristic 1 Sweep tested 950 MHz to 2.25 GHz.

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
1829AC 008U1000	#18 GIFHDLDP SH FR PVC	U1000	31	GRAY	C
1829AC 0091000	#18 GIFHDLDP SH FR PVC	1000	31	WHITE	C
1829AC 0101000	#18 GIFHDLDP SH FR PVC	1000	31	BLACK	C
1829AC 010U1000	#18 GIFHDLDP SH FR PVC	U1000	31	BLACK	C

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 10-23-2003

© 2003 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.